



# IR dryer | Secado IR

## Master 3 EVO

Hoja de especificación de producto

### Características técnicas

Secador portátil de infrarrojos 3 pantallas  
Lámparas 1.100W de onda corta, luz filtrada  
Cuadro de programación digital. 2 funciones: Pre-secado, Secado  
Sensor de distancia  
Encendido de lámparas totalmente independiente.  
Brazo articulado para partes altas. Altura máxima 2m  
Ideal para todos los procesos de repintado  
Potencia máxima: 3.300 W  
Alimentación: 230V 50/60Hz  
Superficie de secado: 1,00m x 1,40 m  
Distancia de trabajo: 50 cm

### Technical features

3 screens infrared dryer  
1.100w lamps , Short Wave, Filtered Light  
Possibility to select active lamps  
Digital Control Panel 2 functions: flash off, full bake  
Proximity Sensor  
Independent IR screen switch  
Articulated arm with hidden pantograph. Maximum height 2m  
Ideal for all repainting processes  
Maximum Power: 3.300 W  
A.C. Input: 220V 50/60 Hz  
Drying surface: 1,00 x 1,40 m  
Working distance: 50cm

Rev 1.2 2015 enero



## IR dryer | Secado IR Master 3 EVO Gold

### Características técnicas

Secador portátil de infrarrojos 3 pantallas  
Lámparas 2.000W de onda corta, luz filtrada  
Cuadro de control computerizado  
7 programas estandarizados y 3 programas personalizables  
Sensor de temperatura  
Sensor de distancia  
Brazo articulado para partes altas. Altura máxima 2m  
Ideal para controlar el proceso de secado en todo momento  
Potencia max: 6.000 W  
Alimentación: 380 V (3F +N+T) 50/60 Hz  
Superficie de secado: 1,40 m x 1 m  
Distancia de trabajo: 50 cm

### Technical features

3 screens infrared dryer  
2.000w infrared lamps, Short Wave, Filtered Light  
Computerized control panel: 7 ready-to-use and 3 personalized programmes  
Proximity Sensor  
Temperature Sensor  
Possibility to select active lamps  
Articulated arm with hidden pantograph  
Maximum height 2m  
Ideal for all repainting processes  
Maximum Power: 6.000 W  
A.C. Input: 380V 50/60 Hz (3F+N+L)  
Working distance: 50 cm

Rev 1.2 2015 enero

